

COLOUR-ENHANCING STAINPROOFING PROTECTOR

CONCRETE, STAMPED CONCRETE, INTERLOCKING
PAVERS, MARBLE CHIP CEMENT TILE



Prevents the formation of dust, stops absorption of dirt and makes cleaning of concrete, stamped concrete, self-locking paving tiles, marble-chip cement tiles.



COVERAGE

With one litre:

10-15 m²

Coverage rates are indicative and per coat.

Packaging

5 litres: boxes of 4.

SHELF LIFE: 5 years

if stored following the indicated storage conditions.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Enhances indoor and outdoor concrete surfaces and protects them against stains and water.
- Creates a barrier that facilitates the removal of oil and grease before they penetrate the surface.
- When applied outdoors on interlocking pavers, marble-chip tiles and stamped concrete, it makes surfaces resistant to weathering.
- Strengthens industrial floors in warehouses, showrooms and garages and makes them dust resistant.
- When applied on residential flooring, the treatment may be completed with a wax finish.

ADVANTAGES

- **Eco-friendly:** does not contain hydrocarbon solvents.
- Reversible treatment
- Consolidating and dust-resistant action
- UV resistant (ASTM G154).
- **Water-based:** not affected by residual humidity, hence drastically reducing on-site work time.

HOW TO USE IT

No dilution required: ready to use.

Shake before use. On a clean and dry surface, apply **CONCRETE SHIELD** uniformly using a flat paintbrush, applicator or roller. On absorbent surfaces, wait 4 hours for the product to dry, and then apply a second coat following the same application instructions.

For indoor domestic environments: 4 hours after the application of **CONCRETE SHIELD**, apply one coat of finishing wax to obtain the desired finish. (**MATT** matte finish or **LONGLIFE** glossy finish).

For outdoor applications: the product should be applied annually to maintain the surface colour enhancement in optimal condition.

Caution:

If the product is applied incorrectly or the surface protection must be entirely restored, remove **CONCRETE SHIELD** with **PS87 PRO**. On indoor residential flooring (micro concrete, quartz concrete, etc.), test the product on small inconspicuous area to check the product's compatibility with the surface before treatment.

On smooth or polished concrete, the product may not adhere correctly. Hence, we recommend testing the product before full application. Do not apply the product outdoors if rain in the forecast. Do not use the product in humid environments or places with standing water. If the product is applied on groutless installations, the protection refers exclusively to the top surface of the tile. Test the colour enhancing effect on a small, inconspicuous area before full application. For regular and special maintenance, do not use alkaline degreasing cleaners. Use only **CLEANER PRO** neutral cleaner.