FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Diamond stone cutter for wet cuts, mitre cuts up to 45°, with GFCI circuit breaker

CS 60 WET

Order number 374.016



Diamond stone cutter for wet cuts, mitre cuts up to 45 $^{\circ}$, with GFCI circuit breaker

- + High-performance motor: extra powerful for stone cutting and joint milling
- + Continuous cut depth setting from 0-60 mm, with rail guide up to 54 mm. In the mitre cut from 0-44 mm, with guide rail up to 38 mm
- + Continuous angle adjustment for mitre cuts from 0-45°
- + Cut marking at the base plate from 0°/30°/45° for rapid orientation
- + High-quality magnesium die-castings for protective cover and base plates
- + Motor protection made of rubber prevents the direct intake of spray water
- + Water supply: for an effective cooling of the diamond blade
- + Quick-fit brass coupling: for 1/2" water hose
- + GFCI operator protector circuit breaker: integrated in cord
- + Ideal for: Inserting water grooves in window sills or steps, work tops, facade slabs, terazzo slabs in garden design & landscaping, joint renovation in the floor
- + Spindle lock

| Technical attributes | |
|--|---------------|
| Power input | 1400 |
| Power output | 840 |
| No load speed | 6200 |
| Diamond cutting disc \emptyset / arbor (inside \emptyset) | 170 / 22,2 mm |
| Cutting depth / with guide rail | 60 / 54 mm |
| Mitre cuttings | 0-45° |
| Depth of cut - mitre cut | 5-44 |
| Depth of cut - mitre cut with guide rail | 0-38 |
| Cable length | 4,0 |
| Weight | 4,5 |
| | |

| Standard equipment | |
|--|---------|
| 1 diamond cutting disc with segmented cutting edge | 347.515 |
| 1 wrench for saw blade change | 359.343 |
| 1 parallel guide fence | 350.613 |
| 1 carrying case L-B0XX® 238 | 414.093 |
| 1 case insert | 436.771 |