

Technical Datasheet - P.V.C Trim

PVC Beading - SRP


Product Description

Attractive yet robust: The rigid but curved design makes it robust enough to finish any installation requiring an internal bead whilst having an attractive appearance. The product can be used on the horizontal or vertical place, around a work surface, or as a skirting on a floor or a coving around a ceiling. Mitre pieces are available for the SRP to provide the perfect finish to the installation.

Dimensions and Colour

Available in 2.5m Lengths and in White Finish

Range



Property	Test Method	Result
Vicat Softening Point	ISO 306	93°C
Tensile Modulus	ASTM D638	1.19 GPa
Yield Stress	ASTM D638	44.8 MPa
Yield Strain	ASTM D638	4.42%
Elongation at Failure	ASTM D638	131%
Flexural Modulus	ISO 178	2.38 GPa
Tensile Impact Strength	ISO 8256	413 kJ/m ²

Allied Products

SRE 2 way external corner, 5 pieces per pack

SRI 2 way internal corner, 5 pieces per pack

SRT 3 way internal corner, 5 pieces per pack

Maintenance

Genesis SRP requires no special maintenance - they should be cleaned periodically using a neutral detergent to maintain the appearance.

Regular cleaning aids the longevity of the profile and ensures there is no corrosion that could affect safety.

Installation

1. Cut to length allowing mitres for corners.
2. Ensure the surfaces that the beading is being applied to are completely clean and free from dust.
3. Use an approximate bead of 5mm of silicone or acrylic on the back of the profile at or around both of the supporting legs. If the product is used around a bath, use silicone to allow for slight movement.

P.V.C. Trim • Stair Nosings • Expansion Joints • Transitions • Seals • Edge Protection • Metal Trim • Skirting • Tools

Tel: +44 (0)1642 713000

Email: info@genesis-gs.com

www.genesis-gs.com

UK Head Office & Factory
Stokesley Business Park Stokesley
North Yorkshire TS9 5JZ UK



Genesis
For the Perfect Finish

