

# ISOMAT SUPERGRUND

## Adhesion primer for roughening smooth or non-absorbent surfaces

### Description

ISOMAT SUPERGRUND is an adhesion primer made of synthetic resins and quartz sand. It is applied on smooth and non-absorbent substrates.

- Water-based and thus suitable for interior use, as it is almost odorless.
- Ready to use.
- Dries quickly.
- Shows high coverage/hiding power.
- Suitable for substrates with in-floor heating.

### Fields of application

ISOMAT SUPERGRUND is used as a ready-to-use primer for roughening the substrate surface, in order to enhance the adhesion of the tile adhesive that is going to be applied. It is also used as a primer of the decorative cement mortars DUROCRET DECO, DUROCRET DECO FLEX, DUROCRET DECO FINISH & ISOMAT ACRYL DECO decorative coating.

It is applied on plenty of smooth and non-absorbent substrates, such as old tiles, marble, natural stone, cement-based industrial floorings, wooden, metal or PVC floorings, tarpaulin (linoleum), as well as anhydride and magnesium screeds.

### Technical data

Form:	liquid
Color:	red
Density:	1.39 kg/l
Successive layer:	1 h at +20°C

### Directions for use

#### 1. Substrate preparation

The substrate to be primed has to be dry and completely free of dust, oil, pollutants etc.

#### 2. Application

Before use, the content of the container should be well stirred until the mixture becomes homogeneous. In case of non-absorbent substrates, ISOMAT SUPERGRUND is poured directly from the container onto the substrate and spread by roller or brush in one thin layer. If after applying the first coating, the surface has not been completely covered with the material, then a second layer should be applied, after the first one has dried.

The adhesive may be applied one hour after priming at +20°C.

In case of absorbent substrates, ISOMAT SUPERGRUND is diluted with pure water at a ratio of up to 1:1, depending on the substrate absorptivity.

ISOMAT SUPERGRUND may then be uniformly applied on the substrate by roller or brush. The adhesive can be applied after the primer has dried.

DUROCRET DECO, DUROCRET DECO FLEX, DUROCRET DECO FINISH layers and ISOMAT ACRYL DECO decorative coating may be applied after the first 24 hours and as long as the primer has completely dried.

### Consumption

100-200 g/m<sup>2</sup>, depending on the substrate absorptivity.

### Packaging

5 kg and 20 kg containers.

### Shelf-life/Storage

12 months from production date, if stored in original unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sun exposure and frost.

# ISOMAT SUPERGRUND

---

## Remarks

- Temperature during the application should be between +5°C and +30°C.
- The primer should be totally dry before applying the next layer.

## Volatile Organic Compounds (VOC)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30 g/l (2010) for the ready-to-use product.

The ready-to-use product ISOMAT SUPERGRUND contains a maximum of 30 g/l VOC.

## ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

**Thessaloniki:** 17th km Thessaloniki - Ag. Athanasios

P.O. BOX 1043, 570 03 Ag. Athanasios

Tel. 2310 576 000 Fax: 2310 722 475

**Athens:** 57th km Athens-Lamia National Road, 32011 Inofita

Tel. 22620 56 406 Fax: 22620 31 644

[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)