# **Safety Data Sheet ULTRACARE EPOXY OFF GEL**

Safety Data Sheet dated: 07/02/2023 - version 3



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: ULTRACARE EPOXY OFF GEL

Trade code: 9011499 UFI: 1RA1-W0YF-H009-407K

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Cleaner Uses advised against: Not available

# 1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsable: sicurezza@mapei.it 1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

## **SECTION 2: Hazards identification**



#### 2.1. Classification of the substance or mixture

# Regulation (EC) n. 1272/2008 (CLP)

Eye Irrit. 2 Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

# 2.2. Label elements

#### Regulation (EC) No 1272/2008 (CLP):

# **Pictograms and Signal Words**



# **Hazard statements**

H319 Causes serious eye irritation.

## **Precautionary statements**

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection. P337+P313 If eye irritation persists: Get medical advice/attention.

# **Special Provisions:**

**EUH208** Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction. Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -**EUH208** 

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

# Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

# 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 1 of 14

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not Relevant

#### 3.2. Mixtures

Mixture identification: ULTRACARE EPOXY OFF GEL

## Hazardous components within the meaning of the CLP regulation and related classification:

| Qty                  | Name   | Ident. Numb.  | Classification   | Registration Number   |
|----------------------|--|---|--|-----------------------|
| ≥20 - <25<br>%       | benzyl alcohol   | CAS:100-51-6<br>EC:202-859-9<br>Index:603-057-<br>00-5    | Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Irrit. 2, H319   | 01-2119492630-38-XXXX |
| ≥2.5 - <5<br>%       | monoethanolamine oleate  | CAS:2272-11-9<br>EC:218-878-0                             | Eye Irrit. 2, H319   |                       |
| ≥1 - <2.5<br>%       | 1-methoxy-2-propanol   | CAS:107-98-2<br>EC:203-539-1<br>Index:603-064-<br>00-3    | Flam. Liq. 3, H226; STOT SE 3,<br>H336   | 01-2119457435-35-XXXX |
| ≥0.49 - <1<br>%      | 2-aminoethanol; ethanolamine   | CAS:141-43-5<br>EC:205-483-3<br>Index:603-030-<br>00-8    | Skin Corr. 1B, H314 STOT SE 3,<br>H335 Acute Tox. 4, H302 Acute<br>Tox. 4, H312 Acute Tox. 4, H332<br>Aquatic Chronic 3, H412  | 01-2119486455-28-XXXX |
|                      |  |   | Specific Concentration Limits:<br>5% ≤ C < 100%: STOT SE 3 H335  |                       |
| ≥0.016 -<br><0.025 % | 1,2-benzisothiazol-3(2H)-one; 1,2<br>benzisothiazolin-3-one  | - CAS:2634-33-5<br>EC:220-120-9<br>Index:613-088-<br>00-6 | H318 Aquatic Acute 1, H400 Acute   |                       |
|                      |  |   | Specific Concentration Limits: $C \ge 0.05\%$ : Skin Sens. 1 H317  |                       |
| <0.0015 %            | reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) | EC:611-341-5<br>Index:613-167-                            | Aquatic Acute 1, H400 Aquatic<br>Chronic 1, H410 Acute Tox. 3,<br>H301 Skin Corr. 1C, H314 Skin<br>Sens. 1A, H317 Acute Tox. 2,<br>H310 Acute Tox. 2, H330 Eye<br>Dam. 1, H318, M-Chronic:100, M-Acute:100       |                       |
|                      |  |   | Specific Concentration Limits: $C \ge 0.6\%$ : Skin Corr. 1C H314 0.06% ≤ C < 0.6%: Skin Irrit. 2 H315 $C \ge 0.6\%$ : Eye Dam. 1 H318 0.06% ≤ C < 0.6%: Eye Irrit. 2 H319 $C \ge 0.0015\%$ : Skin Sens. 1A H317 |                       |

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 2 of 14

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

# 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

# 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

## 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

# 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## **Community Occupational Exposure Limits (OEL)**

OEL Country Occupational Exposure Limit Type

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 3 of 14

benzyl alcohol CAS: 100-51-6

1-methoxy-2-propanol CAS: 107-98-2

National FINLAND Long Term: 45 mg/m3 - 10 ppm

National POLAND Long Term: 240 mg/m3

DFG GERMANY Ceiling - Short Term: 44 mg/m3 - 10 ppm

National GERMANY Long Term: 22 mg/m3 - 5 ppm

NDS POLAND Long Term: 240 mg/m3
National CZECH Long Term: 40 mg/m3

REPUBLIC

National LATVIA Long Term: 5 mg/m3

National CZECH Ceiling - Short Term: 80 mg/m3

**REPUBLIC** 

National BULGARIA Long Term: 5 mg/m3 National LITHUANIA Long Term: 5 mg/m3

National SLOVENIA Long Term: 22 mg/m3 - 5 ppm; Short Term: 44 mg/m3 - 10 ppm

SUVA

Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

National SWEDEN Long Term: 190 mg/m3 - 50 ppm; Short Term: 300 mg/m3 - 75 ppm

SWEDEN, Short-term value, 15 minutes average value

National FINLAND Long Term: 370 mg/m3 - 100 ppm; Short Term: 560 mg/m3 - 150 ppm

FINLAND, hud

National NORWAY Long Term: 180 mg/m3 - 50 ppm

NORWAY, H

NDS Long Term: 180 mg/m3 NDSCh Long Term: 360 mg/m3

National NORWAY Long Term: 185 mg/m3 - 50 ppm; Short Term: 370 mg/m3 - 100 ppm

EU Long Term: 375 mg/m3 - 100 ppm; Short Term: 563 mg/m3 - 150 ppm

Skin

ACGIH Long Term: 50 ppm; Short Term: 100 ppm

A4 - Eye and URT irr

DFG GERMANY Ceiling - Short Term: 740 mg/m3 - 200 ppm
ACGIH Long Term: 50 ppm; Short Term: 100 ppm

A4 - Not Classifiable as a Human Carcinogen; eye and upper respiratory tract irritation

National SWEDEN Long Term: 190 mg/m3 - 50 ppm

National FRANCE Long Term: 188 mg/m3 - 50 ppm; Short Term: 375 mg/m3 - 100 ppm

National SPAIN Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

National GREECE Long Term: 360 mg/m3 - 100 ppm; Short Term: 1080 mg/m3 - 300 ppm

National DENMARK Long Term: 185 mg/m3 - 50 ppm

National FINLAND Long Term: 370 mg/m3 - 100 ppm; Short Term: 560 mg/m3 - 150 ppm

National GERMANY Long Term: 370 mg/m3 - 100 ppm

National PORTUGAL Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm
National NORWAY Long Term: 180 mg/m3 - 50 ppm; Short Term: 225 mg/m3 - 75 ppm
National BELGIUM Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

NDS POLAND Long Term: 180 mg/m3 NDSCh POLAND Short Term: 360 mg/m3

CHE SWITZERLAN Short Term: 720 mg/m3 - 200 ppm

D

NDS NETHERLAND Long Term: 375 mg/m3; Short Term: 563 mg/m3

S

National CZECH Long Term: 270 mg/m3

**REPUBLIC** 

National HUNGARY Long Term: 375 mg/m3; Short Term: 568 mg/m3

Malaysi MALAYSIA Long Term: 369 mg/m3 - 100 ppm

a OEL

National ESTONIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 4 of 14

National LATVIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

National CZECH Ceiling - Short Term: 550 mg/m3

REPUBLIC

National SLOVAKIA Ceiling - Short Term: 568 mg/m3 National SLOVAKIA Long Term: 375 mg/m3 - 100 ppm

National SLOVENIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 562,5 mg/m3 - 150 ppm
National UNITED Long Term: 375 mg/m3 - 100 ppm; Short Term: 560 mg/m3 - 150 ppm

KINGDOM

2-aminoethanol; ethanolamine CAS: 141-43-5 National BULGARIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm
National ROMANIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm
TUR TURKEY Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm
National LITHUANIA Long Term: 190 mg/m3 - 50 ppm; Short Term: 300 mg/m3 - 75 ppm
National CROATIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

EU Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

EU Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

Behaviour Indicative

Possibility of significant uptake through the skin

National BELGIUM Long Term: 184 mg/m3 - 50 ppm; Short Term: 369 mg/m3 - 100 ppm National SLOVENIA Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

National NORWAY Long Term: 2,5 mg/m3 - 1 ppm

ΗE

NDS Long Term: 2,5 mg/m3
NDSCh Long Term: 7,5 mg/m3

National SWEDEN Long Term: 8 mg/m3 - 3 ppm; Short Term: 15 mg/m3 - 6 ppm

SWEDEN, Short-term value, 15 minutes average value

National FINLAND Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

FINLAND, hud

EU Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

Skin

ACGIH Long Term: 3 ppm; Short Term: 6 ppm

Eye and skin irr

DFG GERMANY Ceiling - Short Term: 0,51 mg/m3 - 0,2 ppm
ACGIH Long Term: 3 ppm; Short Term: 6 ppm

eye and skin irritation

EU Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

Behaviour Indicative

Possibility of significant uptake through the skin

National DENMARK Long Term: 2,5 mg/m3 - 1 ppm
National GERMANY Long Term: 0,5 mg/m3 - 0,2 ppm

National PORTUGAL Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

NDS POLAND Long Term: 2,5 mg/m3
NDSCh POLAND Short Term: 7,5 mg/m3

NDS NETHERLAND Long Term: 2,5 mg/m3; Short Term: 7,6 mg/m3

S

National CZECH Long Term: 2,5 mg/m3

REPUBLIC

National HUNGARY Long Term: 2,5 mg/m3; Short Term: 7,6 mg/m3

National CZECH Ceiling - Short Term: 7,5 mg/m3

**REPUBLIC** 

National SLOVAKIA Ceiling - Short Term: 7,6 mg/m3

National ROMANIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National LITHUANIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

ACGIH Long Term: 3 ppm; Short Term: 6 ppm

eye and skin irritation

National SWEDEN Long Term: 2,5 mg/m3 - 1 ppm

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 5 of 14

ΕU Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

Behaviour Indicative

Possibility of significant uptake through the skin

National FRANCE Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National SPAIN Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,5 mg/m3 - 3 ppm National GREECE Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National FINLAND Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National NORWAY Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 5 mg/m3 - 2 ppm National BELGIUM Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

CHF SWITZERLAN Short Term: 10 mg/m3 - 4 ppm

Malaysi MALAYSIA Long Term: 7,5 mg/m3 - 3 ppm

a OEL

National ESTONIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National LATVIA Long Term: 0,5 mg/m3 - 0,2 ppm; Short Term: 7,6 mg/m3 - 3 ppm

National SLOVAKIA Long Term: 2,5 mg/m3 - 1 ppm

National SLOVENIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National UNITED Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

**KINGDOM** 

National BULGARIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm TUR **TURKEY** Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm National CROATIA Long Term: 2,5 mg/m3 - 1 ppm; Short Term: 7,6 mg/m3 - 3 ppm

# Predicted No Effect Concentration (PNEC) values

Exposure Route: Fresh Water; PNEC Limit: 1 mg/l benzyl alcohol

CAS: 100-51-6

Exposure Route: Marine water; PNEC Limit: 0,1 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 5,27 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0,527 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 39 mg/l

Exposure Route: Soil; PNEC Limit: 0,45 mg/kg

Exposure Route: Intermittent release; PNEC Limit: 2,3 mg/l

1-methoxy-2-propanol

CAS: 107-98-2

Exposure Route: Intermittent release; PNEC Limit: 100 mg/l

Exposure Route: Marine water; PNEC Limit: 1 mg/l

Exposure Route: Fresh Water; PNEC Limit: 10 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 52,3 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 5,2 mg/kg

Exposure Route: Soil; PNEC Limit: 4,59 mg/kg

2-aminoethanol: ethanolamine CAS: 141-43-5

CAS: 100-51-6

Exposure Route: Fresh Water; PNEC Limit: 0,085 mg/l

Exposure Route: Marine water; PNEC Limit: 0,0085 mg/l Exposure Route: Intermittent release; PNEC Limit: 0,025 mg/l Exposure Route: Freshwater sediments; PNEC Limit: 0,425 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0,0425 mg/kg

Exposure Route: Soil; PNEC Limit: 0,035 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

# **Derived No Effect Level (DNEL) values**

benzvl alcohol Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 20 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 4 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 6 of Worker Industry: 110 mg/m3; Consumer: 27 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 22 mg/m3; Consumer: 5,4 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

Worker Industry: 40 mg/kg; Consumer: 20 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 8 mg/kg; Consumer: 4 mg/kg

1-methoxy-2-propanol CAS: 107-98-2

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 369 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Professional: 553,5 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Worker Professional: 553,5 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Professional: 183 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Consumer: 43,9 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Consumer: 78 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 33 mg/m3

## 8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid Color: opalescent Odour: Characteristic

Melting point / freezing point: Not available

Initial boiling point and boiling range: 100 °C (212 °F)

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: 100 °C (212 °F)

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: 9.00

Viscosity: Not available

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 7 of 14

Kinematic viscosity: Not available

Solubility in water: yes Solubility in oil: soluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: 1.10 g/cm3 Vapour density: Not available Particle characteristics: Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available No other relevant information

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions

# 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

None in particular.

## 10.6. Hazardous decomposition products

None.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation The product is classified: Eye Irrit. 2(H319)

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

# Toxicological information on main components of the mixture:

benzyl alcohol a) acute toxicity LC50 Inhalation Mist Rat = 11, mg/l 4h

LD50 Oral Rat = 1230, mg/kg

g) reproductive toxicity NOAEL Rat = 1072, mg/m3

1-methoxy-2-propanol a) acute toxicity LD50 Oral Rat = 5300 mg/kg

LD50 Skin Rabbit = 13000 mg/kg

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 8 of 14

LC50 Inhalation Rat = 28,8 mg/l 4h

LD50 Skin Rabbit = 13 g/kg

LC50 Inhalation Rat > 7559 ppm 6h

LD50 Oral Rat = 5000 mg/kg

h) STOT-single exposure NOAEL Oral Rat = 919 mg/kg

NOAEL Inhalation Rat = 3,7 mg/kg NOAEL Skin Rabbit > 1000 mg/kg

2-aminoethanol; ethanolamine

a) acute toxicity

a) acute toxicity

LD50 Oral Rat 2100 mg/kg

LD50 Skin Rabbit 1000 mg/kg

1,2-benzisothiazol-3(2H)- a) acute toxicity

one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 670, mg/kg

reaction mass of: 5-chloro-2-methyl-4-

isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]

LC50 Inhalation Rat = 2,36 mg/l 4h

one [EC no (3:1)

LD50 Skin Rabbit = 660, mg/kg LD50 Oral Rat = 53, mg/kg

#### 11.2. Information on other hazards

# **Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

## List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

## List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

benzyl alcohol CAS: 100-51-6 - a) Aquatic acute toxicity: EC50 Daphnia = 230 mg/L 48

EINECS: 202-859-9 - INDEX: 603-057-00-5

a) Aquatic acute toxicity: LC50 Fish = 770 mg/L 1

a) Aquatic acute toxicity: EC50 Algae = 770 mg/L 72

a) Aquatic acute toxicity: LC50 Fish = 460 mg/L 96

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 460 mg/L 96h

EPA

1-methoxy-2-propanol CAS: 107-98-2 - a) Aquatic acute toxicity: LC50 Fish = 5000 mg/L 96

EINECS: 203-539-1 - INDEX: 603-064-00-3

a) Aquatic acute toxicity : EC50 Daphnia = 23300 mg/L 48

a) Aquatic acute toxicity : EC50 Algae > 1000 mg/L 96

a) Aquatic acute toxicity: LC50 Bacteria > 1000 mg/L 3

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 20.8 g/l 96h IUCLID

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 9 of 14

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 23300 mg/L 48h

2-aminoethanol; ethanolamine

CAS: 141-43-5 - a) Aquatic acute toxicity: EC50 Daphnia = 65 mg/L 48 EINECS: 205-483-3 - INDEX: 603-030-00-8

a) Aquatic acute toxicity: EC50 Algae = 22 mg/L 72 a) Aquatic acute toxicity: LC50 Fish = 349 mg/L 96

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 227 mg/L 96h

a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio = 3684 mg/L 96h

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus 300 mg/L 96h EPA a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss 114 mg/L 96h EPA a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 15 mg/L 72h IUCLID

b) Aquatic chronic toxicity: NOEC Daphnia = 0,85 mg/L

1,2-benzisothiazol-3(2H)-one; 1,2-CAS: 2634-33-5 a) Aquatic acute toxicity: LC50 Fish = 2,15 mg/L benzisothiazolin-3-one - EINECS: 220-

120-9 - INDEX: 613-088-00-6

> b) Aquatic chronic toxicity: NOEC Algae = 0,0403 mg/L 72h b) Aquatic chronic toxicity: EC50 Algae = 0,11 mg/L 72h b) Aquatic chronic toxicity: EC10 Algae = 0,04 mg/L 72h b) Aquatic chronic toxicity: EC50 Daphnia = 3,27 mg/L 48h

NOEC Daphnia = 1,2 mg/L 21d

CAS: 55965-84- a) Aquatic acute toxicity: EC50 Daphnia = 0,12 mg/L 48reaction mass of: 5-chloro-2methyl-4-isothiazolin-3-one [EC 9 - EINECS: no. 247-500-7] and 2-methyl-2H - 611-341-5 isothiazol-3-one [EC no. 220-239- INDEX: 613-167-00-5 6] (3:1)

a) Aquatic acute toxicity: LC50 Fish = 0,22 mg/L 96 a) Aquatic acute toxicity: EC50 Algae = 0,048 mg/L 72 b) Aquatic chronic toxicity: NOEC Algae = 0,0012 mg/L 72

b) Aquatic chronic toxicity: NOEC Daphnia = 0,004 mg/L - 21 d

b) Aquatic chronic toxicity: NOEC Fish = 0,098 mg/L - 28 d

#### 12.2. Persistence and degradability

N.A.

# 12.3. Bioaccumulative potential

N.A.

# 12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

# 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

### 12.7. Other adverse effects

Not available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Print date 09/02/2023 ULTRACARE EPOXY OFF GEL Production Name Page n. 10of 14 Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

#### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

# Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

## **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number or ID number

Not Applicable

#### 14.2. UN proper shipping name

Not Applicable

#### 14.3. Transport hazard class(es)

Not Applicable

#### 14.4. Packing group

Not Applicable

#### 14.5. Environmental hazards

Not Applicable

## 14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

# 14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

#### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 11of 14

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

# Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 30, 40, 75

#### **SVHC Substances:**

SVHC substances not present in a concentration  $\geq$  0.1% (w/w)

#### **National regulations**

Code

H226

H302

3.8/3

4.1/C3

Lagerklasse (TRGS-510): 12 - Non-combustible liquids, that cannot be assigned to any of the aforementioned LGK

#### German Water Hazard Class.

Class 1: slightly hazardous for water.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### **SECTION 16: Other information**

Description

STOT SE 3

Aquatic Chronic 3

Flammable liquid and vapour.

Harmful if swallowed.

| H312   | Harmful in contact with skin.                       |  |  |
|--|---|--|--|
| H314   | Causes severe skin burns and eye damage.            |  |  |
| H319   | Causes serious eye irritation.                      |  |  |
| H332   | Harmful if inhaled.                                 |  |  |
| H335   | May cause respiratory irritation.                   |  |  |
| H336   | May cause drowsiness or dizziness.                  |  |  |
| H412   | Harmful to aquatic life with long lasting effects.  |  |  |
|  |   |  |  |
| Code   | Hazard class and hazard category                    | Description  |  |
| <b>Code</b> 2.6/3                                  | Hazard class and hazard category<br>Flam. Liq. 3    | <b>Description</b> Flammable liquid, Category 3  |  |
|  | •   | •  |  |
| 2.6/3  | Flam. Liq. 3  | Flammable liquid, Category 3   |  |
| 2.6/3<br>3.1/4/Dermal                              | Flam. Liq. 3<br>Acute Tox. 4                        | Flammable liquid, Category 3 Acute toxicity (dermal), Category 4   |  |
| 2.6/3<br>3.1/4/Dermal<br>3.1/4/Inhal               | Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4              | Flammable liquid, Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4                                   |  |
| 2.6/3<br>3.1/4/Dermal<br>3.1/4/Inhal<br>3.1/4/Oral | Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 | Flammable liquid, Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 |  |

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

# Classification according to Regulation Classification procedure (EC) Nr. 1272/2008

3.3/2 Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

Specific target organ toxicity — single exposure, Category 3

Chronic (long term) aquatic hazard, category 3

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 12of 14

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment

CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

 ${\tt IMDG: International\ Maritime\ Code\ for\ Dangerous\ Goods.}$ 

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

**PSG: Passengers** 

 $\hbox{RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.}$ 

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

 $v P v B \colon Very \ Persistent, \ Very \ Bioaccumulative.$ 

WGK: German Water Hazard Class.

#### Paragraphs modified from the previous revision:

- SECTION 3: Composition/information on ingredients

- SECTION 8: Exposure controls/personal protection

- SECTION 9: Physical and chemical properties

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 13of 14

- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Print date 09/02/2023 Production Name ULTRACARE EPOXY OFF GEL Page n. 14of 14