



## **DECLARATION OF PERFORMANCE No 0442**

1. Unique identification code of the product-type: **H40 GEL** 

2. Intended use/es: Improved cementitious adhesive for all internal and external tiling

3. Manufacturer: Tilemaster Adhesives Ltd - Kerakoll Group - Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.

4. System/s of AVCP:

System 3

5. Harmonised standard: BS EN 12004:2007 + A1:2012

Notified body/ies: Lucideon No. 1289

**WARRINGTON FIRE No. 0833** 

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1, d0
Bond strength as:	
initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for:	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Filippo lacconi (General Manager)

At Leyland, on 01/12/2021

Jaimfas

www.tilemasteradhesives.co.uk - www.kerakoll.com