DEVIreg Smart Thermostat





The DEVIreg Smart is an intuitive programmable timer thermostat to be connected to WIFI and DEVIsmart App and controllable from anywhere, at any time. The thermostat is primarily used for controlling electrical floor heating elements. The thermostat is designed for fixed installation only and due to the special designed 2-part construction it fits a wide range of frames and sensors.

The DEVIreg Smart is fast and intuitive to setup using the App wizard. It has an open window detector and energy-saving program including an optimum start/end control ensuring the desired temperature at the correct time and thereby reducing the heating costs.



Benefits

- Wi-Fi Connectivity
- Remote Controllable via
- DEVIsmart App
- Can be paired with up to 10 mobile devices using DEVIsmart App
- Adaptive PWM function
- One DEVIsmart App is able to
- control an unlimited number of locations with DEVIreg Smort
- Can communicate with two mobile devices simultaneously
- Fits many foreign single and multiple frames and competitive NTC sensors

| Туре | Value | |
|--|---|--|
| Operation voltage: | 220 V- 240V~ | |
| Standby power consumption: | Max. 0.4 W | |
| Relay: Resistive load Inductive load | 16A / 3680W @ 230V 1A (Cos Φ = 0.3) | |
| Sensing unit: | NTC 15 kOhm at 25° C, 3m (default) NTC 6.8 kΩ @ 25°C NTC 10 kΩ @ 25°C NTC 12 kΩ @ 25°C NTC 33 kΩ @ 25°C NTC 47 kΩ @ 25°C | |
| Regulation: | PWM – Pulse Width Modulation | |
| Ambient temperature: | 0° C. to 30° C | |
| Frost protection: | 5° C - 9° C (default 5° C) | |
| Floor temperature limit: | Max. 20°C to 35°C (45°C) Min. 10°C to 35°C (45°C) | |
| Temperature range: | 5°C to 35°C (room) 5°C to 45°C (floor) | |
| Storage temperature: | -20°C to +65°C | |
| Cable specification max: | 1 x 4 mm ² or 2 x 2.5 mm ² | |
| Ball pressure test temperature: | 75° C | |
| Pollution degree: | 2 (domestic use) | |
| Controller type: | 1C | |
| Software class: | A | |
| Protection class: | Class II | |
| IP class: | 21 | |
| Dimensions (H x W x D): | 85 mm x 85 mm x 20-24 mm (in-wall depth: 22mm) | |
| Weight: | 127 g | |

| Stock Code | Product Name | Colour | Dimensions (H x W x D) |
|------------|---------------|-------------|------------------------|
| 140F1140 | DEVIreg Smart | Polar White | 85mm x 85mm x 20-24mm |
| 140F1143 | DEVIreg Smart | Pure Black | 85mm x 85mm x 20-24mm |

