









AVAILABLE BLADES































TECHNICAL CHARACTERISTICS





























• For cutting porcelain, single-double fired, marble and granite.

- Maximum length of cut 150 cm (59").
- Maximum depth of cut 100 mm (4") in single pass; 135 mm (5 1/3") in double pass.
- Diamond blade max Ø 350 mm (14"); min Ø 300 mm (12").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.
- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.

- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor assembly holder and pivots in galvanized steel.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- Available accessories: extra side square, self-standing side bench with rollers 4 wheels + 2 handles kit, wheel kit feed.
- ullet Supplied with ø 350 mm (14") diamond disc for porcelain tiles, user manual, keys kit, dressing stone.

MODEL SPECIFICATIONS

HOPE OF ECHICATOR										
Part No.			M	M			•			
224MS 150EU	8024648088635	1	230V 50 Hz	Single-phase	3 HP / 2,2 kW	2800	300 mm 12"	2800		
224MS 150BR	8024648090553	1	230V 60 Hz	Single-phase	3 HP / 2,2 kW	3360	300 mm 12"	3360		
224MS 150US	8024648090560	1	110V 60 Hz	Single-phase	2 HP / 1,5 kW	3360	300 mm 12"	3360		

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT											
Model		:	7 /	\Rightarrow						1	
MISTRAL 150	350 mm 14" 300 mm 12"	100 mm 60 mm	4" 60 mi 2 3/8" 45 m		150 cm 59"	∞	105x105 cm 41 3/8"x 41 3/8"	180x60x h60 cm 71"x23 5/8"x h23 5/8"	73 Kg 160 9 lbs	195x65x h72 cm 77"x25 1/"x h 28 3/8"	90 Kg 198.4 lbs







