

Safety data sheet according to regulation (CE) n. 1907/2006 (REACH), Annex II, and successive adjustments introduced by Commission Regulation (EU) no. 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEANER PRO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Universal floor cleaner.

ı	Identified Uses	Industrial	Professional	Consumer
	Uses	-	*	~
l	1.3. Details of the supplier of the safety data sheet			
l	Name	FILA INDUSTRIA CHIMICA S.	P.A.	
l	Full address	Via Garibaldi, 58		
l	District and Country	35018 San Martino di Lupari ((PD)	
l		ITALIA		
l		Tel. +39.049.9467300		
l		Fax +39.049.9460753		
	e-mail address of the competent person			
l	responsible for the Safety Data Sheet	sds@filasolutions.com		

1.4. Emergency telephone number

For urgent inquiries refer to TEL +39.049.9467300 (Monday –

Friday; 8.30 - 12.30 and 14.00 - 17.30)

UNITED KINGDOM: NHS Direct 111 (In England, Scotland North Ireland) 08454647

(Wales); IRELAND 018092166

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation.

2.2. Label elements



Revision nr. 19

Dated 01/04/2019
Printed on 07/06/2019

Page n. 2/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.

EUH208 Contains:, 1,2-benzisothiazol-3(2H)-one, D LIMONENE

May produce an allergic reaction.

Precautionary statements:

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P280 Wear eye protection / face protection.

P337+P313 If eye irritation persists: Get medical advice / attention.

P264 Wash hands thoroughly after handling.

Less than 5% anionic surfactants 5% or over but less than non-ionic surfactants

15%

perfumes, Citral, Limonene, Preservation agents

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

PROPYLENE GLYCOL MONO

METHYL ETHER

AIR	FILA	Revision nr. 19	
			Dated 01/04/2019
		CLEANER PRO	Printed on 07/06/2019
			Page n. 3/22
			Replaced revision:18 (Dated: 19/02/2
CAS 107-98-2	2≤x< 3	Flam. Liq. 3 H226, STOT SE 3 H336	
EC 203-539-1			
INDEX 603-064-00-3			
Reg. no. 01-2119457435-35			
Alcohols, C12-15, ethoxylated			
CAS 68131-39-5	2≤x< 3	Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Acu Chronic 3 H412	ute 1 H400 M=1, Aquatic
EC		CHIOHIC 3 FI412	
INDEX -			
Reg. no. 01-2119488720-33			
Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts			
CAS 68439-57-6	2 ≤ x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315	
EC			
INDEX -			
Reg. no. 01-2119513401-57			
DIPROPYLENE GLYCOL MONOMETHYL ETHER CAS 34590-94-8	1≤x< 2	Eye Irrit. 2 H319	
EC 252-104-2			
INDEX -			
Reg. no. 01-2119450011-60			
D LIMONENE			
CAS 5989-27-5	$0,1 \le x < 0,15$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H41	
EC 227-813-5		,	
INDEX 601-029-00-7			
Reg. no. 01-2119529223-47			
3,7,-DIMETHYL-2,6-OCTADIENAL			
CAS 5392-40-5	$0.01 \le x < 0.04$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B	H317
EC 226-394-6			
INDEX -			
Reg. no. 01-2119462829-23			
1,2-benzisothiazol-3(2H)-one			
CAS 2634-33-5	$0 \le x < 0.02$	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 Aquatic Acute 1 H400 M=1	H315, Skin Sens. 1 H317,
EC 220-120-9		•	

Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

INDEX 613-088-00-6

CAS 127-91-3

EC 204-872-5 INDEX -

(1S)6,6-DIMETHYL-2-METHYLENBICYCLOHEPTANE

Reg. no. 01-2119519230-54
(1S)2,6,6-TRIMETHYLBICYCLO-2
HEPTENE

 $0 \le x < 0.02$



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 4/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

CAS 7785-26-4

 $0 \le x < 0.02$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin

Sens. 1 H317, Aquatic Chronic 1 H410 M=1

EC 232-077-3

INDEX -

Reg. no. 01-2119979519-16

ETHYL ACETATE

CAS 141-78-6

 $0 \le x < 0.02$

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

INDEX 607-022-00-5

Reg. no. 01-2118475103-46

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove any contact lenses. Wash with warm water for at least 15 minutes, opening the eyelids well. Consult a doctor if the problem persists. SKIN: Remove contaminated clothing. Wash with water. If irritation persists, consult a doctor. Wash the contaminated garments before reusing them. INHALATION: Bring the subject to fresh air. If breathing is difficult, call a doctor immediately.

INGESTION: Consult a doctor. Induce vomiting only upon medical advice. Do not give anything by mouth if the person is unconscious and if not authorized by the doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.


5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.



SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop the leak if there is no danger.

Wear appropriate protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of the skin, eyes and personal clothing. These indications are valid both for workers involved in the work and for emergency interventions. Remove unequipped persons. Use an explosion-proof device. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) or heat from the area where the leak occurred.

6.2. Environmental precautions

Prevent the product from entering sewers, surface waters, water tables.

6.3. Methods and material for containment and cleaning up

For containment

Collect with absorbent substances (sand, diatomaceous earth, binder for acids, universal binder).

For the cleaning

After harvesting, wash the area and the materials involved with water, recovering the water used and, if necessary, sending it to disposal in authorized facilities.

6.4. Reference to other sections

Reference to other sections Personal protection: see section 8 Disposal considerations: see section 13

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters



CLEANER PRO

Revision nr. 19

Dated 01/04/2019 Printed on 07/06/2019

Page n. 6/22

Replaced revision:18 (Dated: 19/02/2019)

Regulatory References:

CZE Česká Republika Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte Deutschland DEU DNK Danmark Graensevaerdier per stoffer og materialer

ESP España

INSHT - Límites de exposición profesional para agentes químicos en España 2017 HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja 2012:5 JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 FIN Suomi FRA

France United Kingdom **GBR**

EH40/2005 Workplace exposure limits
EΦHMEPIΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva
50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról GRC Ελλάδα HRV

Hrvatska

HUN Magyarország

Decreto Legislativo 9 Aprile 2008, n.81 ITA Italia

NLD Nederland Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18

NOR Norge Veiledning om Administrative normer for forurensning i arbeidsatmosfære ROZPORZĄDZENIE MINISTRA RODZIN Y, PRAC Y I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r POL PRT Polska Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos Portugal

trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06

Monitorul Oficial al României 44; 2012-01-19

ROU România SVK Slovensko NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007

SVN Slovenija Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o

varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu

SWE Sverige

Occupational Exposure Limit Values, AF 2011:18 KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733 TUR Türkiye

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive ΕU OEL EU

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH **ACGIH 2018**

PROPYLENE GLYCO	L MONO METHYL ETHER
Thursday and Linett Value	

Threshold Limit V							
Туре	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
TLV	CZE	270		550		SKIN	
AGW	DEU	370	100	740	200		
MAK	DEU	370	100	740	200		
TLV	DNK	185	50				
VLA	ESP	375	100	568	150	SKIN	
HTP	FIN	370	100	560	150	SKIN	
VLEP	FRA	188	50	375	10	SKIN	
WEL	GBR	375	100	560	150	SKIN	
TLV	GRC	360	100	1080	300		
GVI	HRV	375	100	568	150	SKIN	
AK	HUN	375		568			
VLEP	ITA	375	100	568	150	SKIN	
OEL	NLD	375		563		SKIN	
TLV	NOR	180	50			SKIN	
NDS	POL	180		360			
VLE	PRT	375	100	568	150		
TLV	ROU	375	100	568	150	SKIN	
NPHV	SVK	375	100	568		SKIN	
MV	SVN	375	100	562,5	150	SKIN	

AIR		FILA INI	DUSTRIA	CHIMICA	S.P.A.		Revision nr. 19	
							Dated 01/04/2019	
			CLEANE	R PRO			Printed on 07/06/2019	
			OLLAND				Page n. 7/22	
							Replaced revision:18 (Dat	ted: 19/02/201
MAK	SWE	190	50	300	75	SKIN		
ESD	TUR	375	100	568	150	SKIN		
OEL	EU	375	100	568	150	SKIN		
TLV-ACGIH		184	50	368	100			
Predicted no-effect concen	tration - PNEC							
Normal value in fresh wate	r			10	mg	1/I		
Normal value in marine wa	ter			1	mg	ı/l		
Normal value for fresh water	er sediment			52,3		/ g/kg/d		
Normal value for marine wa	ater sediment			5,2		ı/kg/d		
Normal value for water, into	ermittent release			100	mg	ı/l		
Normal value of STP micro				100	mg	ı/l		
Health - Derived no-ef	Effects on	DMEL			Effects on workers			
	consumers				WOIKEIS			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
		Acute systemic	Chronic local VND	systemic 3,3 mg/kg		Acute systemic		Chronic systemic
Route of exposure Oral Inhalation		Acute systemic		systemic				systemic
Oral		Acute systemic	VND	systemic 3,3 mg/kg bw/d				
Oral Inhalation Skin Sulfonic acids, C14-16	Acute local 6 (even numbered)-		VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d	Acute local	systemic	553,5 mg/m3	systemic 369 mg/m3 50,6 mg/kg
Oral Inhalation Skin	Acute local 6 (even numbered)- tration - PNEC		VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d	Acute local	systemic	553,5 mg/m3	369 mg/m3 50,6 mg/kg
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa	Acute local 6 (even numbered)- tration - PNEC ater sediment		VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d en numbered)	-alkene, sodiu	systemic um salts	553,5 mg/m3	369 mg/m3 50,6 mg/kg
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on	alkane hydroxy a	VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d en numbered)	-alkene, sodiumg	systemic um salts	553,5 mg/m3	369 mg/m3 50,6 mg/kg
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I	alkane hydroxy a	VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d en numbered)	-alkene, sodiu mg	um salts //kg	553,5 mg/m3 VND Chronic local	369 mg/m3 50,6 mg/kg bw/d Chronic
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers	alkane hydroxy a	VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg bw/d 18,1 mg/kg bw/d en numbered) 2025 42 Chronic systemic 12.95	-alkene, sodiumg	systemic um salts //kg	553,5 mg/m3 VND Chronic local	369 mg/m3 50,6 mg/kg bw/d
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-ef Route of exposure Oral	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers	alkane hydroxy a	VND VND VND Chronic local	systemic 3,3 mg/kg bw/d 43,9 mg/kg bw/d 18,1 mg/kg bw/d en numbered)	-alkene, sodiumg	um salts //kg	553,5 mg/m3 VND Chronic local	369 mg/m 50,6 mg/kg bw/d Chronic systemic
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers	alkane hydroxy a	VND VND VND Chronic local VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg bw/d 18,1 mg/kg bw/d en numbered): 2025 42 Chronic systemic 12.95 mg/kg/d	-alkene, sodiumg	um salts //kg	553,5 mg/m3 VND Chronic local	369 mg/m 50,6 mg/kg bw/d
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local	alkane hydroxy a	VND VND VND Chronic local VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3	-alkene, sodiumg	um salts //kg	553,5 mg/m3 VND Chronic local	Systemic 369 mg/m3 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin DIPROPYLENE GLYC Threshold Limit Value	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local	alkane hydroxy a	VND VND VND Chronic local VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3	-alkene, sodiumg	um salts //kg	553,5 mg/m3 VND Chronic local	Systemic 369 mg/m3 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local	alkane hydroxy a DMEL Acute systemic	VND VND VND Chronic local VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3 1295 mg/m3	-alkene, sodiumg	um salts //kg	553,5 mg/m3 VND Chronic local	Systemic 369 mg/m; 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin DIPROPYLENE GLYCC Threshold Limit Value Type	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local	Acute systemic ETHER TWA/8h	VND VND VND Chronic local VND VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3 1295 mg/m3	-alkene, sodiumg mg Effects on workers Acute local	um salts //kg	553,5 mg/m3 VND Chronic local VND VND	Systemic 369 mg/m; 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin DIPROPYLENE GLYC Threshold Limit Value Type TLV	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local OL MONOMETHYL Country	alkane hydroxy a DMEL Acute systemic ETHER TWA/8h mg/m3	VND VND VND Chronic local VND VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3 1295 mg/m3 STEL/15min mg/m3	-alkene, sodiumg mg Effects on workers Acute local	wm salts //kg //I Acute systemic	553,5 mg/m3 VND Chronic local VND VND	Systemic 369 mg/m; 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33
Oral Inhalation Skin Sulfonic acids, C14-16 Predicted no-effect concen Normal value for marine wa Normal value for water, inte Health - Derived no-eff Route of exposure Oral Inhalation Skin DIPROPYLENE GLYC Threshold Limit Value	Acute local 6 (even numbered)- tration - PNEC ater sediment ermittent release fect level - DNEL / I Effects on consumers Acute local OL MONOMETHYL Country	Acute systemic ETHER TWA/8h mg/m3 270	VND VND VND Chronic local VND VND VND	systemic 3,3 mg/kg bw/d 43,9 mg/kg 18,1 mg/kg bw/d 2025 42 Chronic systemic 12.95 mg/kg/d 45,04 mg/m3 1295 mg/m3 STEL/15min mg/m3 550	-alkene, sodiumg mg Effects on workers Acute local	wm salts //kg //I Acute systemic	553,5 mg/m3 VND Chronic local VND VND	Systemic 369 mg/m3 50,6 mg/kg bw/d Chronic systemic 152,22 mg/m3 2158,33

HTP

VLEP

WEL

TLV

FIN

FRA

GBR

GRC

310

308

308

600

50 50

50

100

900

150

SKIN

SKIN

AIN		FILA IN	DUSTRIA	CHIMICA	S.P.A.		Revision nr. 19	
							Dated 01/04/2019	
			CLEANE	R PRO			Printed on 07/06/2019	
			OLLAND				Page n. 8/22	
							Replaced revision:18 (Da	ated: 19/02/2019)
AK	HUN	308		308				
VLEP	ITA	308	50			SKI	N	
TLV	NOR	300	50			SKI	N	
NDS	POL	240		480				
VLE	PRT	308	50			SKI	N	
TLV	ROU	308	50			SKI	N	
NPHV	SVK	308	50			SKI	N	
MV	SVN	308	50			SKI	N	
MAK	SWE	300	50	450	75	SKI	N	
ESD	TUR	308	50			SKI	N	
OEL	EU	308	50			SKI	N	
TLV-ACGIH		606	100	909	150	SKI	N	
Predicted no-effect concentr	ation - PNEC							
Normal value in fresh water				19	mg	ı/l		
Normal value in marine water	r			1,9	mg	ı/l		
Normal value for fresh water	sediment			70,2	mg	ı/kg		
Normal value for marine wat	er sediment			7,02	mg	J/kg		
Normal value for water, inter	mittent release			190	mg	ı/l		
Normal value of STP microo	rganisms			4168	mg	ı/l		
Normal value for the terrestr	al compartment			2,74	mg	J/kg		
Health - Derived no-effe	Effects on	DMEL			Effects on			
Route of exposure	consumers Acute local	Acute systemic	Chronic local	Chronic systemic	workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	36 mg/kg bw/d				
Inhalation			VND	37,2 mg/m3			VND	308 mg/m3
Skin			VND	121 mg/kg bw/d			VND	283 mg/kg/c
D LIMONENE Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	28						

0,014

0,0014

3,85

0,385

1,8

133

0,763

mg/l

mg/l

mg/kg

mg/kg

mg/l

mg/kg

mg/kg/d

Predicted no-effect concentration - PNEC

Normal value for fresh water sediment

Normal value of STP microorganisms

Normal value for marine water sediment

Normal value for the terrestrial compartment

Normal value for the food chain (secondary poisoning)

Normal value in fresh water

Normal value in marine water

FILA INDUSTRIA CHIMICA S.P.A. Revision nr. 19 ДIR Dated 01/04/2019 Printed on 07/06/2019 **CLEANER PRO** Page n. 9/22 Replaced revision:18 (Dated: 19/02/2019) NPI Normal value for the atmosphere Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers workers Route of exposure Chronic local Chronic Acute Chronic local Chronic Acute systemic Acute local Acute local systemic systemic systemic Oral VND NPI VND 4,8 mg/kg hw/d NPI NPI NPI NPI NPI NPI 66,7 mg/m3 Inhalation 16,6 mg/m3 Skin NPI NPI NPI 4,8 mg/kg VND NPI VND 9,5 mg/kg bw/d bw/d 3,7,-DIMETHYL-2,6-OCTADIENAL **Threshold Limit Value** Туре Country TWA/8h STEL/15min mg/m3 mg/m3 ppm ppm OFI FU 5 1,2-benzisothiazol-3(2H)-one Predicted no-effect concentration - PNEC Normal value in fresh water 0,011 mg/l Normal value in marine water 1.1 ma/l Normal value for fresh water sediment 0.0499 mg/kg Normal value for marine water sediment 0,0049 mg/kg Normal value for water, intermittent release 0,000403 mg/l Normal value for the terrestrial compartment 3 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers workers Acute systemic Route of exposure Chronic local Chronic Acute Chronic local Chronic Acute local Acute local systemic systemic systemic 6,81 mg/m3 Inhalation 1.2 ma/m3 0,345 mg/kg 0,966 mg/kg Skin bw/d bw/d (1S)2,6,6-TRIMETHYLBICYCLO-2 HEPTENE **Threshold Limit Value** Type Country TWA/8h STEL/15min mg/m3 ppm mg/m3 ppm OEL EU 20 Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers workers Route of exposure Chronic local Chronic Chronic local Chronic Acute local Acute systemic Acute local Acute systemic systemic systemic Inhalation

5,98 mg/m3

STEL/15min

ppm

ma/m3

(1S)6,6-DIMETHYL-2-METHYLENBICYCLOHEPTANE

Health - Derived no-effect level - DNEL / DMEL

Country

EU

TWA/8h

mg/m3

ppm

20

Threshold Limit Value

Type

OEL



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 10/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation		•						5.98 mg/m3

ETHYL ACETATE						
Threshold Limit Val	Country	TWA/8h		STEL/15min		
··	<u> </u>	mg/m3	ppm	mg/m3	ppm	
TLV	CZE	700		900		
AGW	DEU	1500	400	3000	800	
MAK	DEU	1500	400	3000	800	
TLV	DNK	540	150			
VLA	ESP	1460	400			
HTP	FIN	1100	300	1800	500	
VLEP	FRA	1400	400			
WEL	GBR		200		400	
TLV	GRC	1400	400			
GVI	HRV		200		400	
AK	HUN	1400		1400		
OEL	NLD	550		1100		
TLV	NOR	550	150			
NDS	POL	734		1468		
TLV	ROU	400	111	500	139	
NPHV	SVK	1500	400	3000		
MV	SVN	1400	400	1400	400	
MAK	SWE	500	150	1100	300	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 184 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 11/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following must be considered for the final choice of the work glove material: compatibility, degradation, break time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as unpredictable. The gloves have a wear time that depends on the duration and the mode of use

Recommended material: Nitrile, minimum 0.38 mm thickness or equivalent protective barrier material with a high level performance for continuous contact conditions, with a minimum permeability time of 480 minutes in accordance with the CEN EN 420 and EN standards 374.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid
Colour yellow

Odour Lemon fragrance
Odour threshold Not determined

pH 10,1 Melting point / freezing point $< 0 \, ^{\circ}\text{C}$ Initial boiling point $> 100 \, ^{\circ}\text{C}$ Boiling range Not available Flash point $> 61 \, ^{\circ}\text{C}$

Evaporation Rate

Flammability of solids and gases

Lower inflammability limit

Upper inflammability limit

Lower explosive limit

Not determined

Not applicable



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 12/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

Upper explosive limit Not applicable Vapour pressure Not determined Vapour density Not determined Solubility Readily soluble Partition coefficient: n-octanol/water Not determined Auto-ignition temperature Not applicable Decomposition temperature Not determined Viscosity Not determined Explosive properties not applicable Oxidising properties not applicable

9.2. Other information

VOC (Directive 2010/75/EC): 4,09 % - 41,13 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

PROPYLENE GLYCOL MONO METHYL ETHER

Dissolves various plastic materials. Stable in normal conditions of use and storage.

Absorbs and disolves in water and in organic solvents. With air it may slowly form explosive peroxides.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react with: oxidising substances. When heated to decomposition releases: harsh fumes, zinc alloys.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.


10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

PROPYLENE GLYCOL MONO METHYL ETHER



May react dangerously with: strong oxidising agents, strong acids.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

PROPYLENE GLYCOL MONO METHYL ETHER

Avoid exposure to: air.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

PROPYLENE GLYCOL MONO METHYL ETHER

Incompatible with: oxidising substances, strong acids, alkaline metals.

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.


SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information



Information not available

Information on likely routes of exposure

PROPYLENE GLYCOL MONO METHYL ETHER

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

PROPYLENE GLYCOL MONO METHYL ETHER

The main route of entry is the skin, while the respiratory route is less important, given the low vapor pressure of the product. Above 100 ppm there is irritation of the ocular, nasal and oropharyngeal mucous membranes. At 1000 ppm there is a disturbance in the balance and severe irritation to the eyes. The clinical and biological tests performed on the exposed volunteers did not reveal any anomalies.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:
Not classified (no significant component)
LD50 (Oral) of the mixture:
>2000 mg/kg
LD50 (Dermal) of the mixture:
Not classified (no significant component)

1,2-benzisothiazol-3(2H)-one

LD50 (Oral) 454 mg/kg rat linee guida 401 per il test OECD

LD50 (Dermal) > 2000 mg/kg rat linee guida 402 per il test OECD

Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts

LD50 (Oral) 2079 mk/kg ratto maschile femminile

LD50 (Dermal) > 13500 mg/kg coniglio

LC50 (Inhalation) > 52 mg/l 4 ore

Alcohols, C12-15, ethoxylated

LD50 (Oral) 1700 mg/kg ratto maschile femminile

LD50 (Dermal) > 2000 mg/kg ratto maschile femminile



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019
Page n. 15/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

DIPROPYLENE GLYCOL MONOMETHYL ETHER

LD50 (Oral) 2410 mg/kg mouse male (fasted)

LD50 (Dermal) 2764 mg/kg rabbit

LC50 (Inhalation) > 29 ppm/1h 2h rat

PROPYLENE GLYCOL MONO METHYL ETHER

LD50 (Oral) 4016 mg/kg Rat male/female

LD50 (Dermal) 13000 mg/kg Rabbit

LC50 (Inhalation) 54,6 mg/l/4h Rat

D LIMONENE

LD50 (Oral) > 2000 mg/kg rat female OCSE 423

LD50 (Dermal) > 5000 mg/kg rabbit

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.Contains:1,2-benzisothiazol-3(2H)-one D LIMONENE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 16/22 Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1,2-benzisothiazol-3(2H)-one

LC50 - for Fish 1,6 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 2,9 mg/l/48h Daphnia Magna OECD TG 202

EC50 - for Algae / Aquatic Plants 0,11 mg/l/72h Pseudokirchneriella subcapitata OECD TG 201

Alcohols, C12-15, ethoxylated

EC10 for Algae / Aquatic Plants 0,092 mg/l/72h alghe 72 h

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

LC50 - for Fish 1300 mg/l/96h Lepomis machrochirus EC50 - for Crustacea > 1919 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 969 mg/l/72h Scenedesmus subspicatus

PROPYLENE GLYCOL MONO METHYL

ETHER

LC50 - for Fish 20800 mg/l/96h Pimephales promelas EC50 - for Crustacea 23300 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 500 mg/l/72h Scenedesmus subspicatus

D LIMONENE

LC50 - for Fish 0,72 mg/l/96h Pimephales promelas OCSE 203 EC50 - for Crustacea 0,51 mg/l/48h Daphnia magna OECD 202

EC50 - for Algae / Aquatic Plants 0,32 mg/l/72h pseudokirchneriella subcapitata OECD 201

Chronic NOEC for Fish 0,37 mg/l Pimephales promelas 8d OECD 212



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 17/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

Chronic NOEC for Crustacea

0,08 mg/l Daphnia magna 21d OECD 211

12.2. Persistence and degradability

Sulfonic acids, C14-16 (even numbered)alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts Rapidly degradable

Alcohols, C12-15, ethoxylated

Rapidly degradable

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

85% 28d

PROPYLENE GLYCOL MONO METHYL

ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

96% 28d

ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

D LIMONENE

Rapidly degradable 80% 28d OECD 301D

12.3. Bioaccumulative potential

1,2-benzisothiazol-3(2H)-one

BCF 6,62 Lepomis macrochirus

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

Partition coefficient: n-octanol/water 0,056

PROPYLENE GLYCOL MONO METHYL


ETHER

Partition coefficient: n-octanol/water < 1

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68 BCF 30

12.4. Mobility in soil



Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

		Tp :: 49
AIR	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 19
		Dated 01/04/2019
	CLEANER PRO	Printed on 07/06/2019
	CLLANER PRO	Page n. 19/22
		Replaced revision:18 (Dated: 19/02/2019)
Not applicable		
14.5. Environmental hazards		
Not applicable		
14.6. Special precautions for user		
Not applicable		
14.7. Transport in bulk according to	Annex II of Marpol and the IBC Code	
Information not relevant		
SECTION 15. Regulatory	information	
15.1. Safety, health and environme	ental regulations/legislation specific for the substance or mixture	
Seveso Category - Directive 2012/18/E	EC: None	
Restrictions relating to the product or o	contained substances pursuant to Annex XVII to EC Regulation 1907/2006	
Product Point	3 - 40	
Substances in Candidate List (Art. 59	REACH)	
On the basis of available data, the pro-	duct does not contain any SVHC in percentage greater than 0,1%.	
Substances subject to authorisation (A	nnex XIV REACH)	
None		
Substances subject to exportation repo	orting pursuant to (EC) Reg. 649/2012:	
None		
Substances subject to the Rotterdam (Convention:	
None		
Substances subject to the Stockholm (Convention:	
None		



Revision nr. 19

Dated 01/04/2019

Printed on 07/06/2019

Page n. 20/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

PROPYLENE GLYCOL MONO METHYL ETHER

DIPROPYLENE GLYCOL MONOMETHYL ETHER

D LIMONENE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4
Asp. Tox. 1 Aspiration hazard, category 1
Eye Dam. 1 Serious eye damage, category 1
Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2Skin irritation, category 2Skin Sens. 1Skin sensitization, category 1Skin Sens. 1BSkin sensitization, category 1B

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.



Revision nr. 19

Dated 01/04/2019 Printed on 07/06/2019

Page n. 21/22

Replaced revision:18 (Dated: 19/02/2019)

CLEANER PRO

H315 Causes skin irritation

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.


EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website



- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 03 / 04 / 06 / 08 / 16.