according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



**BUILDING TRUST** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Everbuild All Purpose Silicone Spray

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild - A Sika Company

Site 41

**Knowsthorpe Way** 

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

# 1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.


#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**







Print Date 02.05.2019







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other igni-

tion source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane</li>

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

## Components

•			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Hydrocarbons, C6-C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 40 - < 60
isoalkanes, cyclics, <5% n-	921-024-6	Skin Irrit. 2; H315	
hexane	01-2119475514-35-	STOT SE 3; H336	
	XXXX	Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**





Revision Date 06.12.2018

Version 4.0

Print Date 02.05.2019

Substances with a workplace exposure limit :				
petroleum gases, liquefied	68476-85-7 270-704-2	Flam. Gas 1; H220	>= 40 - < 60	

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Erythema

Dermatitis
Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.

May cause drowsiness or dizziness.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



Unsuitable extinguishing

media

: Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

**BUILDING TRUST** 

courses.

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

## 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.


Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure.

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

BUILDING TRUST

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

# 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
petroleum gases, liquefied	68476-85-7	TWA	1.000 ppm 1.750 mg/m3	GB EH40		
Further information		Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if LPG contains more than 0.1% of buta-1,3-diene.				
		STEL	1.250 ppm 2.180 mg/m3	GB EH40		
Further information	· ·	Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if LPG contains more than 0.1% of buta-1.3-diene.				

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

: Chemical-resistant, impervious gloves complying with an ap-Hand protection

Country GB 100000010883

5 / 13

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**





Print Date 02.05.2019

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, Skin and body protection

long-sleeved working clothing, long trousers).

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

**Appearance** : aerosol

Colour off-white

Odour hydrocarbon-like

Odour Threshold No data available

No data available

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flash point -60 °C

Method: closed cup

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



BUILDING TRUST

: No data available Flammability (solid, gas)

Upper explosion limit / Upper : 7,4 %(V)

flammability limit

Lower explosion limit / Lower : 1,1 %(V)

flammability limit

Vapour pressure 34,6637 hPa

Relative vapour density : No data available

: ca. 0,8 g/cm3 (20 °C) Density

Solubility(ies)

: No data available Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic Not applicable

Explosive properties No data available

Oxidizing properties : No data available

# 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**





Version 4.0

Print Date 02.05.2019

#### 10.5 Incompatible materials

Revision Date 06.12.2018

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

# Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

# Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

May cause drowsiness or dizziness.

# STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

# 12.2 Persistence and degradability

No data available

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



# 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

**BUILDING TRUST** 

0.1% or higher...

#### 12.6 Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number

ADR : UN 1950 IMDG : UN 1950 IATA : UN 1950

## 14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



ADR : AEROSOLS IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2 IMDG : 2.1 IATA : 2.1

14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Country GB 100000010883

Sika\*

BUILDING TRUST

rint Date 02.05.2019

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**



# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

BUILDING TRUST

**(=> 0.1 %)**.

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: petroleum gases, liquefied (Number

on list 29)

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 100 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content:

100 %, 800 g/l

VOC content excluding water

according to Regulation (EC) No. 1907/2006



# **Everbuild All Purpose Silicone Spray**

Revision Date 06.12.2018 Version 4.0 Print Date 02.05.2019

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

#### Other regulations:

75/324/EEC

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

**Aquatic Chronic** Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Flam. Gas Flammable gases Flam. Liq. Flammable liquids Skin irritation Skin Irrit.

STOT SE Specific target organ toxicity - single exposure GB EH40 UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period) GB EH40 / STEL Short-term exposure limit (15-minute reference period)

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

**GHS** Globally Harmonized System

**IATA** International Air Transport Association

International Maritime Code for Dangerous Goods **IMDG** 

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

according to Regulation (EC) No. 1907/2006

# **Everbuild All Purpose Silicone Spray**





Print Date 02.05.2019

Revision Date 06.12.2018 Version 4.0

**PBT** Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

**REACH** Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

Very persistent and very bioaccumulative vPvB

#### **Further information**

#### Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Calculation method Skin Irrit. 2 H315 Calculation method STOT SE 3 H336 Calculation method Aquatic Chronic 2 H411 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN